



High Output Version



Eco Version

# Audible Signals - Industrial ECO TLM AUDIBLE MODULES



Tel +31(0)85-27 36 750  
Fax +31(0)85-27 36 760  
Web www.inrato.com

## Industrial LED-TLM Eco Tower Light > Audible Modules

### Product overview

These audible modules have been designed for use in conjunction with the Moflash LED-TLM Eco Tower Light Module range. They are a simple fix addition that offers an audible warning signal in addition to the multiple visual ones that the tower offers.

The module can be pre-set with either a pulsed or continuous tone. The Eco buzzers have been designed for local indication only but a higher decibel output version (Ac only) is available.

This has two dB outputs selectable by a slide switch inside the enclosure.

### Features



- Continuously rated
- Low current consumption
- Cost effective audible solution
- Quick & easy installation or upgrade

### Material

Black ABS Plastic



### ECO TLM-AUD-02 >

**Code No:** LED-TLM-AUD-02  
**Voltage:** 24v Dc ---  
**Operating Temperature:** -25 to +55 °C  
**Current:** 55mA  
**Pulsed Tone Rate:** 60/80 (time/min)  
**Output dB:** 100  
**IP Protection:** IP65






### ECO TLM-AUD-04 >

**Code No:** LED-TLM-AUD-04  
**Voltage:** 85-275v Ac ~  
**Operating Temperature:** -25 to +55 °C  
**Current:** <55mA  
**Output dB:** 80  
**IP Protection:** IP54



### HIGH OUTPUT TLM-AUD120-04 >

**Code No:** LED-TLM-AUD120-04  
**Voltage:** 85-275v Ac ~  
**Operating Temperature:** -25 to +55 °C  
**Current:** <20  
**Output dB:** 100-120 selectable  
**IP Protection:** IP65



APPROVALS and  
CONFORMITIES

